





### Flat Webbing Sling










Flat Webbing Sling Without Capacity Stripes

1. 100% high tensile polyester material
2. According to EN 1492-1:2000
3. With reinforced lifting eyes
4. Safety factor: 7:1
5. Low elongation
6. Length available: 1m up to 10m
7. Wear resistant
8. Other safety factors available: 5:1 6:1 8:1
9. Single ply or double plies

#### 吊眼类型 Lifting eye types

1、平吊眼 / Flat eye	
2、翻转吊眼 / Reversed eye	
3、单边折叠吊眼 Folded eye width from 1 side	
4、双边折叠吊眼 Folded eye width from 2 side	
5、1/3 宽度折叠吊眼 Folded eye 1/3 width	






Webbing Width (mm)	Color code According to EN 1492-1	Working load limited with one webbing sling					Working load limited with two webbing slings			
		(Tons)					(Tons)			
		Straight lift	Choked lift	$\beta$			Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
				0°-7°	7°-45°	45°-60°				
										
1.00	0.80	2.00	1.40	1.00	1.40	1.12	1.00	0.80		
25	WLL1T	1.00	0.80	2.00	1.40	1.00	1.40	1.12	1.00	0.80
50	WLL2T	2.00	1.60	4.00	2.80	2.00	2.80	2.24	2.00	1.60
75	WLL3T	3.00	2.40	6.00	4.20	3.00	4.20	3.36	3.00	2.40
100	WLL4T	4.00	3.20	8.00	5.60	4.00	5.60	4.48	4.00	3.20
125	WLL5T	5.00	4.00	10.00	7.00	5.00	7.00	5.60	5.00	4.00
150	WLL6T	6.00	4.80	12.00	8.40	6.00	8.40	6.72	6.00	4.80
200	WLL8T	8.00	6.40	16.00	11.20	8.00	11.20	8.96	8.00	6.40
250	WLL10T	10.00	8.00	20.00	14.00	10.00	14.00	11.20	10.00	8.00

**Flat Webbing Sling With Capacity Stripes**










Endless webbing sling

1. 100% high tensile polyester material
2. According to EN 1492-1:2000
3. With reinforced lifting eyes
4. Safety factor: 7:1
5. Each stripe is equal to 1 ton capacity
6. Low elongation
7. Wear resistant
8. Length available: 1m up to 10m
9. Other safety factors available: 5:1 6:1 8:1
10. Single ply or double ply

**吊眼类型 Lifting eye types**

1、平吊眼 / Flat eye	
2、翻转吊眼 / Reversed eye	
3、单边折叠吊眼 Folded eye width from 1 side	
4、双边折叠吊眼 Folded eye width from 2 side	
5、1/3 宽度折叠吊眼 Folded eye 1/3 width	

























Webbing Width (mm)	Color code According to EN 1492-1	Working load limited with one webbing sling					Working load limited with two webbing slings			
		(Tons)					(Tons)			
		Straight lift	Choked lift	$\beta$			Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
				0°-7°	7°-45°	45°-60°				
										
1.0	0.8	2.0	1.4	1.0	1.4	1.1	1.0	0.8		
30	WLL1T	1.000	0.800	2.000	1.400	1.000	1.400	1.120	1.000	0.800
60	WLL2T	2.000	1.600	4.000	2.800	2.000	2.800	2.240	2.000	1.600
90	WLL3T	3.000	2.400	6.000	4.200	3.000	4.200	3.360	3.000	2.400
120	WLL4T	4.000	3.200	8.000	5.600	4.000	5.600	4.480	4.000	3.200
150	WLL5T	5.000	4.000	10.000	7.000	5.000	7.000	5.600	5.000	4.000
180	WLL6T	6.000	4.800	12.000	8.400	6.000	8.400	6.720	6.000	4.800
240	WLL8T	8.000	6.400	16.000	11.200	8.000	11.200	8.960	8.000	6.400
300	WLL10T	10.000	8.000	20.000	14.000	10.000	14.000	11.200	10.000	8.000

**Endless webbing sling**

1. 100% high tensile polyester material
2. Safety factor available 2:1,5:1,6:1,7:1
3. Low elongation
4. Wear resistant
5. Length available:1m up to 10m
6. Single ply or double ply














Webbing Width (mm)	Color code According to EN 1492-1	Working load limited with one webbing sling							Working load limited with two webbing slings			
		Straight lift	Choked lift	(Tons)					Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
				$\beta$								
				0°-7°	7°-45°	45°-60°	up to 45°	45°-60°				
												
		<b>1.00</b>	<b>0.80</b>	<b>2.00</b>	<b>1.40</b>	<b>1.00</b>	<b>0.70</b>	<b>0.50</b>	<b>1.40</b>	<b>1.12</b>	<b>1.00</b>	<b>0.80</b>
30	WLL1T	1.00	8.00	2.00	1.40	1.00	0.70	0.50	1.40	1.12	1.00	8.00
60	WLL2T	2.00	1.60	4.00	2.80	2.00	1.40	1.00	2.80	2.24	2.00	1.60
90	WLL3T	3.00	2.40	6.00	4.20	3.00	2.10	1.50	4.20	3.36	3.00	2.40
120	WLL4T	4.00	3.20	8.00	5.60	4.00	2.80	2.00	5.60	4.48	4.00	3.20
140	WLL5T	5.00	4.00	10.00	7.00	5.00	3.50	2.50	7.00	5.60	5.00	4.00
180	WLL6T	6.00	4.80	12.00	8.40	6.00	4.20	3.00	8.40	6.72	6.00	4.80
240	WLL8T	8.00	6.40	16.00	11.20	8.00	5.60	4.00	11.20	8.96	8.00	6.40
300	WLL10T	10.00	8.00	20.00	14.00	10.00	8.40	6.00	14.00	11.20	10.00	8.00

Webbing Width (mm)	Color code According to EN 1492-1	Working load limited with one webbing sling							Working load limited with two webbing slings			
		(Tons)							(Tons)			
		Straight lift	Choked lift	$\beta$					Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
				0°-7°	7°-45°	45°-60°	up to 45°	45°-60°				
												
		<b>1.00</b>	<b>0.80</b>	<b>2.00</b>	<b>1.40</b>	<b>1.00</b>	<b>0.70</b>	<b>0.50</b>	<b>1.40</b>	<b>1.12</b>	<b>1.00</b>	<b>0.80</b>
25	WLL1T	1.00	8.00	2.00	1.40	1.00	0.70	0.50	1.40	1.12	1.00	8.00
50	WLL2T	2.00	1.60	4.00	2.80	2.00	1.40	1.00	2.80	2.24	2.00	1.60
75	WLL3T	3.00	2.40	6.00	4.20	3.00	2.10	1.50	4.20	3.36	3.00	2.40
100	WLL4T	4.00	3.20	8.00	5.60	4.00	2.80	2.00	5.60	4.48	4.00	3.20
125	WLL5T	5.00	4.00	10.00	7.00	5.00	3.50	2.50	7.00	5.60	5.00	4.00
150	WLL6T	6.00	4.80	12.00	8.40	6.00	4.20	3.00	8.40	6.72	6.00	4.80
200	WLL8T	8.00	6.40	16.00	11.20	8.00	5.60	4.00	11.20	8.96	8.00	6.40
250	WLL10T	10.00	8.00	20.00	14.00	10.00	8.40	6.00	14.00	11.20	10.00	8.00

## Round Sling



1. 100% high tensile polyester material
2. According to EN 1492-1:2000
3. Safety factor: 7:1
4. Each stripe is equal to 1ton capacity
5. Low elongation
6. Flexible and wear resistant
7. Length available: 1m up to 10m
8. Other safety factors available: 5:1 6:1 8:1
9. Single ply or double plies

Color code According to EN 1492-1	Working load limited with one webbing sling							Working load limited with two webbing slings			
	(Tons)							(Tons)			
	Straight lift	Choked lift	$\beta$					Straight lift up to 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
			0°-7°	7°-45°	45°-60°	up to 45°	45°-60°				
											
	1.00	0.80	2.00	1.40	1.00	0.70	0.50	1.40	1.12	1.00	0.80
WLL1T	1.00	8.00	2.00	1.40	1.00	0.70	0.50	1.40	1.12	1.00	8.00
WLL2T	2.00	1.60	4.00	2.80	2.00	1.40	1.00	2.80	2.24	2.00	1.60
WLL3T	3.00	2.40	6.00	4.20	3.00	2.10	1.50	4.20	3.36	3.00	2.40
WLL4T	4.00	3.20	8.00	5.60	4.00	2.80	2.00	5.60	4.48	4.00	3.20
WLL5T	5.00	4.00	10.00	7.00	5.00	3.50	2.50	7.00	5.60	5.00	4.00
WLL6T	6.00	4.80	12.00	8.40	6.00	4.20	3.00	8.40	6.72	6.00	4.80
WLL8T	8.00	6.40	16.00	11.20	8.00	5.60	4.00	11.20	8.96	8.00	6.40
WLL10T	10.00	8.00	20.00	14.00	10.00	7.00	5.00	14.00	11.20	10.00	8.00
WLL12T	12.00	9.60	24.00	16.80	12.00	8.40	6.00	16.80	13.44	12.00	9.60